
Archgard

GAS STOVE Direct Vent / Freestanding



45 DVFS28N

Quality, Design, Dependability

Achieve that perfect traditional look you've been seeking for your home by adding an efficient and convenient Archgard Freestanding Gas stove. Whether replacing a wood burning stove, adding a rustic touch to your home, or bringing that unique design to life, the 45 DVFS28N provides the ambiance you've been seeking.

Input Rating	
Natural Gas	18,750-28,000 BTU/hr 5.5 -8.2 kW/hr
Propane	19,600-28,000 BTU/hr 5.7-8.2 kW/hr
Efficiencies	
Steady State	67.69%
P4 Fireplace Efficiency	57.84%

STANDARD FEATURES

Included

Included Welded/rivet and

Included

Optional

*All fireplaces come standard with barrier screens which attach to the

gasket, silicone free

Elite Limited Lifetime Wall to wall steel pan

w/ Lifetime Warranty

36"

DOORS & GRILLS



Black Grills Standard

PANEL SET OPTIONS

45- BRPL-QCR / Québec City Red



Gold Grills (Optional)

45-BRPL-QCG /




Nickel Grills (Optional)

45-BRPL-RG / Eternal Flame Reflective Ceramic Glass



TECHNICAL DIMENSIONS

FRONT VIEW (445mm) 111



642mm

TOP VIEW



door with very little effort.

Ceramic Glass

Barrier Screen

Warranty

Burner Type


Fan Kit

Firebox Construction


Propane Conversion Kit

Minimum Chimney height from

top of unit to center of elbow on horizontal termination



Corner Installation



A minimum of 3' (914 mm) of vertical vent to center of elbow is required for a maximum horizontal run of 3' (914 mm).



Part # 100-3050

7' (178mm)

> Archgard Fireplace Products 7116 Beatty Drive Mission BC V2V 6B4 archgard.com March 27, 2019

15.75" (400mm)



